

SUBFLOOR ADHESIVE



STOPS FLOOR SQUEAKS



10X

MORE COVERAGE
COMPARED TO 28 OZ
CAULK ADHESIVES

- ▶ High tensile & shear strength
- ▶ Expands to fill voids between the joist & subfloor
- ▶ Dry & wet climate

SUBFLOOR ADHESIVE



ASTM D3498 | APA-AFG-01 | UL Classified

TYTAN Professional Subfloor Adhesive prevents floor squeaks by filling gaps between subfloor and joists, reducing strain on mechanical fasteners.

HOW IT WORKS

Upon application, TYTAN Subfloor Adhesive immediately reduces to a gel, then slowly expands over 48 hours to fill the voids and provide a strong, squeak-free bond to lumber, plywood, joists, trusses, decking, concrete, metals, masonry and other substances.

- Prevents floor squeaks
- Works on wet or frozen surfaces
- Easy and fast installation
- No solvents



Formulated for installing:

- OSB
- Plywood
- Treated lumber
- Composite decking
- Many other construction materials

RECOMMENDED FOR USE WITH TYTAN 39" LONG BARREL GUN

TYTAN's 39" long-barrel applicator allows users to install this product from a standing position, reducing strain on the back, knees and hands compared to traditional caulk adhesive applicators. It has an extra-long barrel and heavy duty metal construction design.

